## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: SanicoPolux

**Supplier's address:** Sanico Electronics Polska Sp. z o.o., Okólna 45, 05-270 Marki Marki mazowieckie, PL

## Model identifier: 312723

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED LAMP				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		Energy efficiency class	G			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500			
On-mode power (P <sub>on</sub> ), expressed in W	72,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	-			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer Height	65	Spectral power	See image			
dimensions Width	430	distribution in the	in last page			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	430	range 250 nm to 800 nm, at full-load			
Claim of equivale	ent power <sup>(a)</sup>	-	lf yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	-		
Parameters for LED and OLED light sources:						
R9 colour renderi	ing index value	-	Survival factor	-		
the lumen mainte	enance factor	-				
Parameters for LED and OLED mains light sources:						
displacement fact	tor (cos φ1)	-	Colour consistency in McAdam ellipses	-		
Claims that an source replaces light source with ballast of a partic Flicker metric (Pst	a fluorescent out integrated cular wattage.	_(b) _	If yes then replacement claim (W) Stroboscopic effect	-		
There include (F3)			metric (SVM)			

(a)'-' : not applicable;

(b)'-' : not applicable;